

HALLMARK

Manufacturers, Distributors & Importers.

Shop.no.1, Susheela aptms, plot 36/8,
sector 8A, Behind hp gas godown,
Airoli, Navi-mumbai-400708
e-mail: hallmark.supply@gmail.com
Contact no.09322211917



Creating Our Future From a Single Drop
ThreeBond International, Inc.



1100,1300 series(Liquid gaskets)

It is a liquid material that seals various types of flanges and pipes with threads. We have a wide selection of grades so that you can choose the right one for the condition of the application site.

Product name	Features and Uses	Appearance	Viscosity (Pa·S)	Blow out resistance (MPa room temperature)
TB1102	Non-drying	Yellow	7	9.5
TB1110F	Anaerobic, lubricating	White	50	9.8
TB1121	Non-solvent, removable	Gray	300	9
TB1141G	Water-base, chemical resistance	Gray	15	10 and higher
TB1158	Heat resistant, gear oil resistant, acrylic type FIPG	Black	200	10 and higher
TB1184	Semi-drying, oil resistant, chemical resistant	Gray	9.5	10



2300 series(Threelock and sealock processes to prevent leaks and loosening of threads)

By applying the sealant to the threads of bolts and so on, the threads themselves will have sealing capability. Once treated, a seal is achieved by merely tightening the screws.

Product name	Features and Uses	Appearance
TB2358	Heat-resistant seal, fluorine-based	White
TB2365B	Reusable, adjustment screws / nylon	Green
TB2365C	Reusable, adjustment screws / nylon	Red

1200 series (Silicone-based liquid adhesives and seals, potting agents)



1200 series (Silicone-based liquid adhesives and seals, potting agents)

Once cured, it forms a rubber elastic body, and it has excellent vibration absorption property as well as shock- and heat- resistance.

Product name	Features and Uses	Appearance	Viscosity (Pa·S)	Blow out resistance (MPa room temperature)
TB1207B	Heat resistant and LLC resistant	Black	100	10 and higher
TB1211	Multipurpose silicone	White	68	10 and higher
TB1215	Heat resistant, oil resistant, gearoil resistant	Gray	20	10 and higher
TB1216E	Oil resistant, LLC resistant	Gray	200	10 and higher
TB1217F	Oil resistant, LLC resistant	Gray	210	10 and higher
TB1217H	Initial resistance to pressure, oil resistant	Gray	330	10 and higher
TB1217M	Oily surface adhesion, Heat resistant, oil resistant	Black	280	10 and higher
TB1281	Gear oil resistant, heat resistant	reddish brown	100	10 and higher
TB1281B	AT fluid resistant, heat resistant	reddish brown	115	10 and higher